

Access Control | Readykey™ K2010 Proximity Keyfob

Overview

The K2010 Keyfob is compatible with the Stanley GS3, Readykey K2000-series and Easikey reader and credential range. Unobtrusive and compact it fits on a key ring and can be easily incorporated into any existing Stanley PAC Access, Readykey™ for Windows or PAC Vision security management software, and is often used where photo ID is not required.

As an alternative to the traditional mechanical key, millions of Stanley PAC proximity cards and fobs are used by people as an easy and reliable means of gaining access to their places of work and other secured access points e.g. car park barriers and turnstiles.

The passive proximity technology in the Keyfob requires no batteries or physical contact with the reader; this helps assure that the keyfobs are virtually wear-free and will provide years of service with no maintenance backed by a lifetime guarantee. Robust, world-class construction combined with advanced technology and a pre-programmed unique identification number without site codes, makes programming easy and copying almost impossible.

Together with the access control system, the Keyfob enables a user's movements to be monitored and the building protected. The Keyfob need only be held near the proximity door reader for the code to be read and access granted or denied within 0.5 of a second. In the event that the keyfob is lost or stolen, it can easily be replaced and the lost keyfob access privileges, simply and instantly revoked.

Key Features

- Offers fast and convenient access
- Small and convenient
- Rugged and durable 'washing machine tough' design
- Versatile, easily attached to a keyring, badge clip, chain or carried in pocket or handbag
- Compatible with all Stanley PAC 125 kHz GS3/KeyPAC and Readykey™ 153 kHz K2000-series readers
- Proven and reliable technology
- High security, offering over a billion unique code combinations.
Card numbers are embedded and tracked in the manufacturing process ensuring that card numbers are never duplicated.
- Double sealed and ultra-sonic welded ABS construction
- Proven, Reliable 153 kHz Technology
- Long life, passive no battery design
- Compatible replacement for the EK71 Easikey Keyfob
- Lifetime guarantee



FEATURES AND SPECIFICATIONS CHART

	K2010 Proximity Keyfob
Description	Uniquely coded, 153 kHz, proximity keyfob
ID Technology	Readykey/PAC 153 kHz
Dimensions	H: 2.40 in. L: 1.10 in. D: 0.20 in.
Weight	0.32 oz. nominal
Operating Temperature	-18° to 131°F
Keyfob Outer Construction	Double sealed ultrasonic welded ABS plastic
Keyfob Inner Construction	RF core fully encapsulated in epoxy
Finish Front	Black matt plastic with PAC logo cap
Finish Rear	Black matt plastic
Warranty	Limited Lifetime warranty against defects in materials and workmanship .
Ordering Information Stanley PAC Part Number (Supplied in pack of 10)	75-K2010 Proximity Keyfob



CREDENTIAL READ RANGE

	Keyfob	ISO Card
Oneprox Standard Reader	Up to 4.7 in.	Up to 7 in.

PAC CREDENTIALS



K2010
OLD STYLE



K2010



EK71



K2011

