

## Access Control | KeyPAC K3010 Proximity Keyfob

### Overview

The KeyPAC K3010 Fob is compatible with the entire Stanley PAC 125 kHz GS3 and KeyPAC reader and credential range. Unobtrusive and compact it fits on a key ring and can be easily incorporated into any existing Stanley PAC security management software, where photo ID is not required.

As an alternative to the traditional mechanical key, millions of Stanley PAC proximity cards and fobs are used by people as an easy and reliable means of gaining access to their places of work and other secured access points e.g. car park barriers and turnstiles.

The passive proximity technology in the Keyfob requires no batteries or physical contact with the reader; this helps assure that the keyfobs are virtually wear-free and will provide years of service with no maintenance backed by a lifetime guarantee. Robust, world-class construction combined with advanced technology and a pre-programmed unique identification number without site codes, makes programming easy and copying almost impossible.

Together with the access control system, the Keyfob enables a user's movements to be monitored and the building protected. The Keyfob need only be held near a GS3 Proximity door reader for the code to be read and access granted or denied within 0.5 of a second. In the event that the keyfob is lost or stolen, it can easily be replaced and the lost keyfob access privileges, simply and instantly revoked.

### Key Features

- Offers fast and convenient access
- Small and convenient
- Rugged and durable 'washing machine tough' design
- Versatile, easily attached to a keyring, badge clip, chain or carried in pocket or handbag
- Compatible with all Stanley PAC 125 kHz GS3/KeyPAC and Readykey™ 153 kHz K2000-series readers
- High security, offering over a billion unique code combinations.  
Card numbers are embedded and tracked in the manufacturing process ensuring that card numbers are never duplicated.
- Proven and reliable technology
- Double sealed and ultra-sonic welded ABS construction
- Proven, Reliable 125 kHz Technology
- Long life, passive no battery design
- Lifetime guarantee



## FEATURES AND SPECIFICATIONS CHART

	K3010 Proximity Keyfob
Description	Uniquely coded, 125 kHz, oval shaped proximity keyfob
ID Technology	KeyPAC - 125 kHz
Dimensions	H: 2.40 in. L: 1.22 in. D: 0.35 in.
Weight	0.32 oz. nominal
Operating Temperature	-18° to 131°F
Keyfob Outer Construction	Double sealed ultrasonic welded ABS plastic
Keyfob Inner Construction	RF core fully encapsulated in epoxy
Finish Front	Black matt plastic with key design
Finish Rear	Black matt plastic
Warranty	Limited Lifetime warranty against defects in materials and workmanship .
Ordering Information Stanley PAC Part Number (Supplied in pack of 10)	<b>75-K3010</b> KeyPAC Proximity Keyfob



## CREDENTIAL READ RANGE

	Keyfob	ISO Card
Oneprox Standard Reader	Up to 4.7 in.	Up to 7 in.


## KEYPAC CREDENTIALS



K3010



K3011



K3011M

